



2 BODY MORTUARY CHAMBER (FULLY SS304GRADE







Capacity	Two Body Capacity
Temperature Range	Temperature between -2°C to 5°C
Temperature controller	Complete digital temperature controlled
Safety feature	Safety feature alarm 3 types and up to 7 types can be incorporated
Lock system	Magnetic gasket door is provided with key lock system

TECHNICAL SPECIFICATION:

- Imported mute totally enclosed type compressor with individual chamber
- Magnetic gasket door is provided with key lock system
- Complete digital temperature controlled
- 3 way telescopic system for Cadaver trays which is a proprietary feature
- Temperature between -2°C to 5°C
- Bi sonic Fan motor
- Imported copper vaporizer cooling pipeline which can guarantee long life
- Fluoride free totally enclosed type UNI processor & single cycle refrigeration system
- Inbuilt lithium accumulator which will keep displaying the temperature and basic 48 hours post electricity failure.
- Safety feature alarm 3 types and up to 7 types can be incorporated
- 1055 mm(W) x 2400 mm (D) x 1785 mm (H)
- Weight: 150 kgs
- ISO 9001, ISO 13485, CE marked, WHO GMP Certified
- Compatible Stabilizer should be installed with the machine.

Authorised Distributor:



Registered Head Office

Sarba Mangala Pally, NH34, Adjacent to ICICI Bank P.O & Dist: Malda -732101(West Bangal) +91 98310 63341

sukarma.hmd@gmail.com

North East Branch Office

Bylane No. 9, House No- 5, Ground Floor, RGB Road , Zoo Road, Tiniali, Guwahati- 781024



